



**Manufacturers and distributors of sealing
and Jointing Materials**

DATA / SPECIFICATION SHEET

NOVUS 40

DESCRIPTION

Novus 40 is a good quality compressed sheet material based on a blend of aramid and inorganic fibres with a rubber binder system.

SERVICE

Novus 40 is a general purpose material suitable for use in wide range of applications, including hot and cold water, steam, oils, fuels, gases and a wide range of general chemicals.

AVAILABILITY

Thickness range = 0.4mm to 3.0mm

Standard sheet sizes = 2.0m x 2.0m, 2.0m x 1.5m, 2.0m x 1.0m, 1.5m x 1.5m, 1.5m x 1.0m.

Standard roll sizes = Up to a maximum size of 6.0m x 2.0m

Available with fine mesh mild steel reinforcement:
Novus 40 Metallic.

Can also be supplied with anti-stick coating and graphite coating.




Colour - White

TYPICAL PHYSICAL PROPERTIES

Thickness		1.5mm
Density		2.0g/cc
Tensile Strength	ASTM F152	12MPa
Compression	ASTM F36	9%
Recovery	ASTM F36	50%min
Residual Stress	BS7531 (300°C) DIN 52913	20MPa 29MPa
Gas Leakage	BS 7531	<1.0cc/min
ASTM Oil 1	Thickness Increase	10%
IRM 903 Oil	Thickness Increase	20%
ASTM Fuel B	Thickness Increase	20%

Novus 40



- 1 Suitable subject to chemical compatibility
- 2 Suitable in some cases but check your application requirements with Novus
- 3 Contact the Novus Technical Team for applications with higher temperatures and pressures. Applicable to 1.5mm and below.

The operating temperature of non-asbestos sheet material is related to the thickness of materials selected. Thinner materials give better temperature and pressure properties.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company.

Novus Sealing (Thailand) Co., Ltd. : 135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Ratchadaphisek Rd., Bangkok 10400 THAILAND

Tel +66-0-2689-5393 to 6 Fax +66-0-2689-5397 to 8 www.novusthailand.com E-Mail: enquiry@novusthailand.com