

# A Better Seal for the Environment

# DATA/SPECIFICATION SHEET

### Colour - Blue

# NOVUS 45

### DESCRIPTION

Novus 45 is a medium quality cost effective compressed sheet material manufactured from virgin fibres and recycled material, with a nitrile rubber binder system.

### SERVICE

Novus 45 is a general purpose material suitable for use with oils, solvents, gases, water, low pressure steam and most dilute acids and alkalis.

## APPROVALS/COMPLIANCE

TA-LUFT (in accordance with VDI Guideline 2440)

Α	V	Α	П	L	Α	В	П	L	П	П	Υ

Thickness range = 0.4mm to 6.0mm


Standard sheet sizes = 2.0 m x 2.0 m, 2.0 m x 1.5 m, 2.0 m x 1.0 m, 1.5 m x 1.5 m, 1.5 m x 1.0 m.


Standard roll sizes = Up to a maximum size of 6.0 m x 2.0 m

Available with gauze mild steel wire reinforcement: Novus 45 GWI.

Can also be supplied with anti-stick coating and graphite coating.

TYPICAL	PHYSICAL PRO	PERTIES
Thickness		1.5mm
Density		1.9g/cc
Tensile Strength	ASTM F152	12MPa
Compression	ASTM F36	10%
Recovery	ASTM F36	50%min
Residual Stress	BS7531 (300°C)	18MPa
	DIN 52913	23MPa
Gas Leakage	BS 7531	<1.0cc/min
ASTM Oil 1	Thickness Increase	2.0%
IRM 903 Oil	Thickness Increase	5.0%
ASTM Fuel B	Thickness Increase	6.0%





Suitable in some cases but check your application requirements with Novus

Contact the Novus Technical Team for applications with higher temperatures and pressures. Applicable to 1.5mm and below.

The operating temperature of non-asbestos sheet material is related to the thickness of materials selected. Thinner materials give better temperature and pressure properties.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only and without liability on the part of the company.

Novus Sealing (Thailand) Co., Ltd.: 135/18 Amornphan 205 Tower 2 Bldg., 8th Flr., Ratchadaphisek Rd., Bangkok 10400 THAILAND